



## Industrial Blue Elastic Rubber Caster

**Product #** F08334

**Load Capacity Per Caster** Max. 150 kg

**Wheel Diameter** 100 mm

**Total Height** 128 mm

**Tread Width** 35 mm

**Fastening Type** Fixed

**Axle Diameter** 12 mm

**Axle Length** 40 mm

**Mounting Hole Diameter** 9 mm

**Mounting Plate Dimensions** 3 7/16 in x 4 in (87 mm x 102 mm)

### DESCRIPTION

#### Non-marking rubber tread

Blue non-marking runner tread. These heavy-duty casters are durable and designed for use in the most demanding environments. Available in fixed or swivel design, with several braking options.

### ADVANTAGES AND BENEFITS

- Double-lock braking system for both the wheel and the swivel (F08336, F08339, and F24800) - Non-marking rubber tread - Low starting effort, rolls easily; tread does not flat-spot - Metal thread guards - Grease seal to hold in lubricant - Corrosion-resistant zinc finish

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F08334
<b>Mounting Type</b>	Plate
<b>Material</b>	Elastic Rubber
<b>Recommended Surfaces</b>	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
<b>Finish</b>	Blue
<b>Conditions</b>	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

