



Industrial Blue Elastic Rubber Caster

Product # F08336

Load Capacity Per Caster Max. 150 kg

Wheel Diameter 100 mm

Total Height 128 mm

Tread Width 35 mm

Fastening Type Swivel with Double-Lock Brake

Axle Diameter 12 mm

Axle Length 40 mm

Mounting Hole Diameter 9 mm

Mounting Plate Dimensions 3 5/32 in x 4 1/8 in (80 mm x 105 mm)

DESCRIPTION

Non-marking rubber tread

Blue non-marking runner tread. These heavy-duty casters are durable and designed for use in the most demanding environments. Available in fixed or swivel design, with several braking options.

ADVANTAGES AND BENEFITS

- Double-lock braking system for both the wheel and the swivel (F08336, F08339, and F24800) - Non-marking rubber tread - Low starting effort, rolls easily; tread does not flat-spot - Metal thread guards - Grease seal to hold in lubricant - Corrosion-resistant zinc finish

TECHNICAL SPECIFICATIONS

Product #	F08336
Mounting Type	Plate
Material	Elastic Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Blue
Conditions	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

