



Flat-Free

Product # F21154

Dynamic Load Capacity Max. 100 kg

Wheel Diameter 200 mm

Tread Width 57 mm

Tread Type Sawtooth

Hub Type Centered

Hub Width 50 mm

Hub Specification Metal/Centered

Axle Length 50 mm

DESCRIPTION

Puncture-free, no pressure loss, no flats

ADVANTAGES AND BENEFITS

- Puncture-free, no pressure loss, no flats - Light, ideal for extreme cold - Made of microcellular polyurethane foam - Greased for easy maintenance - Offered with centered or offset rims, according to type of use

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|---|
| Product # | F21154 |
| Recommended Surfaces | Asphalt, Steel/Grills, Concrete, Wood/Planking, Gravel, Grass |
| Color / Finish | Black, Green |
| Material | Polyurethane Foam |
| Axle Diameter | 16 mm |
| Hub Material | Metal |

IMPORTANT INFORMATION

Wheel size F21578: 4.80/4.00-8 F21152 and F21679: 4.10/3.50-4 F21154 and F21579: 2.80/2.50-4 F21683 and F21680: 4.00-6

APPLICATION

8 in (2.80/2.50-4) for dollies and trolleys 10 in (4.10/3.50-4) most used wheel size for dollies 13 in (4.00-6) for wheelbarrows and dollies 16 in (4.80/4.00-8) most used wheel size for wheelbarrows Can also be used for air compressors, log splitters, lightweight trailers, etc., 8 in (2.80/2.50-4) for dollies and trolleys

PRODUCT PHOTOS

