



Flat-Free

Product # F21579

Dynamic Load Capacity Max. 100 kg

Wheel Diameter 200 mm

Tread Width 57 mm

Tread Type Studded

Hub Type Off-centered

Hub Width 60 mm

Hub Specification Metal/Offset

Axle Length 50 mm

DESCRIPTION

Puncture-free, no pressure loss, no flats

ADVANTAGES AND BENEFITS

- Puncture-free, no pressure loss, no flats - Light, ideal for extreme cold - Made of microcellular polyurethane foam - Greased for easy maintenance - Offered with centered or offset rims, according to type of use

TECHNICAL SPECIFICATIONS

Product #	F21579
Recommended Surfaces	Asphalt, Steel/Grills, Concrete, Wood/Planking, Gravel, Grass
Color / Finish	Black, Green
Material	Polyurethane Foam
Axle Diameter	16 mm
Hub Material	Metal

IMPORTANT INFORMATION

Wheel size F21578: 4.80/4.00-8 F21152 and F21679: 4.10/3.50-4 F21154 and F21579: 2.80/2.50-4 F21683 and F21680: 4.00-6

APPLICATION

8 in (2.80/2.50-4) for dollies and trolleys 10 in (4.10/3.50-4) most used wheel size for dollies 13 in (4.00-6) for wheelbarrows and dollies 16 in (4.80/4.00-8) most used wheel size for wheelbarrows Can also be used for air compressors, log splitters, lightweight trailers, etc., 8 in (2.80/2.50-4) for dollies and trolleys

PRODUCT PHOTOS

