



# **Gray Thermoplastic Rubber Casters for General Use**

**Product #** F24786

Load Capacity Per Caster Max. 75 kg

Wheel Diameter 75 mm

Total Height 100 mm

Tread Width 24 mm

Fastening Type Swivel Without Brake

**Mounting Plate Dimensions** 2 3/8 in x 2 3/8 in (60 mm x 60 mm)

### **DESCRIPTION**

Non-marking rubber tread

Medium-duty caster. Scuff-free gray thermoplastic rubber with plate. Swivel with full locking brake.

#### ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Metal thread guards - Corrosion-resistant zinc finish - Two independent rows of hardened polished precision ball bearings roll freely in large-diameter lubricated raceways

#### **TECHNICAL SPECIFICATIONS**

Product #	F24786
Mounting Type	Plate
Material	TPR (Thermoplastic Rubber)
Recommended Surfaces	Concrete, Carpet, Steel, Wood/Planking, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Gray
Conditions	Water, Solvents, Detergent, Extreme Heat, Petroleum Products

## IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

#### **DISCLAIMER**

Technical data subject to change without prior notice.



# PRODUCT PHOTOS

