



Industrial Blue Elastic Rubber Caster

Product # F24789

Load Capacity Per Caster Max. 250 kg

Wheel Diameter 160 mm

Total Height 190 mm

Tread Width 45 mm

Fastening Type Swivel Without Brake

Axle Diameter 20 mm

Axle Length 59 mm

Mounting Hole Diameter 11 mm

Mounting Plate Dimensions 4 11/32 in x 5 5/16 in (110 mm x 135 mm)

DESCRIPTION

Non-marking rubber tread

Blue non-marking runner tread. These heavy-duty casters are durable and designed for use in the most demanding environments. Available in fixed or swivel design, with several braking options.

ADVANTAGES AND BENEFITS

- Double-lock braking system for both the wheel and the swivel (F08336, F08339, and F24800) - Non-marking rubber tread - Low starting effort, rolls easily; tread does not flat-spot - Metal thread guards - Grease seal to hold in lubricant - Corrosion-resistant zinc finish

TECHNICAL SPECIFICATIONS

Product #	F24789
Mounting Type	Plate
Material	Elastic Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Blue
Conditions	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

