



## Euro Series Industrial Rubber Casters

**Product #** F24790

**Load Capacity Per Caster** Max. 50 kg

**Wheel Diameter** 80 mm

**Total Height** 105 mm

**Tread Width** 25 mm

**Fastening Type** Swivel Without Brake

**Axle Diameter** 12 mm

**Axle Length** 40 mm

**Mounting Hole Diameter** 8.5 mm

**Mounting Plate Dimensions** 3 5/32 in x 4 1/32 in (80 mm x 102 mm)

### DESCRIPTION

#### Superior rolling quality

These Euro series industrial rubber casters are suitable for surfaces that have water, detergent, petroleum, or by-products. Available with fixed, swivel, or double locking plate.

### ADVANTAGES AND BENEFITS

- Metal thread guard - Double-lock braking system for both the wheel and the swivel (F24801, F24802, and F24803) - Grease seal holds in lubricant - Corrosion-resistant zinc finish - Fully seated ball bearing eliminates the need for axle lubrication, thus reducing maintenance costs - Two independent rows of hardened, polished precision ball bearings roll freely in large-diameter lubricated raceways

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F24790
<b>Mounting Type</b>	Plate
<b>Material</b>	Euro Series Rubber
<b>Recommended Surfaces</b>	Concrete, Steel, Wood/Planking, Asphalt
<b>Finish</b>	Black
<b>Conditions</b>	Water, Detergent, Petroleum Products

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

