



Euro Series Industrial Rubber Casters

Product # F24792

Load Capacity Per Caster Max. 100 kg

Wheel Diameter 125 mm

Total Height 155 mm

Tread Width 37 mm

Fastening Type Swivel Without Brake

Axle Diameter 15 mm

Axle Length 49 mm

Mounting Hole Diameter 8.5 mm

Mounting Plate Dimensions 3 5/32 in x 4 1/32 in (80 mm x 102 mm)

DESCRIPTION

Superior rolling quality

These Euro series industrial rubber casters are suitable for surfaces that have water, detergent, petroleum, or by-products. Available with fixed, swivel, or double locking plate.

ADVANTAGES AND BENEFITS

- Metal thread guard - Double-lock braking system for both the wheel and the swivel (F24801, F24802, and F24803) - Grease seal holds in lubricant - Corrosion-resistant zinc finish - Fully seated ball bearing eliminates the need for axle lubrication, thus reducing maintenance costs - Two independent rows of hardened, polished precision ball bearings roll freely in large-diameter lubricated raceways

TECHNICAL SPECIFICATIONS

Product #	F24792
Mounting Type	Plate
Material	Euro Series Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS