



## Industrial Polyamide Rubber Caster

**Product #** F24805

**Total Height** 162 mm

**Fastening Type** Swivel Without Brake

**Mounting Plate Dimensions** 3 11/32 in x 4 1/8 in (85 mm x 105 mm)

### DESCRIPTION

#### Non-marking rubber tread

Industrial polyamide rubber caster. These heavy-duty casters are designed for use in the most demanding environments. Available with fixed plate, swivel, or double locking.

### ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Low starting effort, rolls easily - Double-lock braking system locks both the wheel and the swivel (F24804) - High impact-resistant polyamide inner and outer rings; shock-absorbing central rubber ring

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F24805
<b>Load Capacity Per Caster</b>	Max. 200 kg
<b>Wheel Diameter</b>	125 mm
<b>Tread Width</b>	35 mm
<b>Mounting Type</b>	Plate
<b>Material</b>	Polyamide
<b>Recommended Surfaces</b>	Concrete, Carpet, Wood/Planking, Asphalt
<b>Finish</b>	Beige, Blue
<b>Axle Diameter</b>	8 mm
<b>Axle Length</b>	44 mm
<b>Mounting Hole Diameter</b>	9 mm
<b>Conditions</b>	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

