



## Gray Thermoplastic Rubber Casters for General Use

**Product #** F24815

**Load Capacity Per Caster** Max. 75 kg

**Wheel Diameter** 75 mm

**Total Height** 100 mm

**Tread Width** 24 mm

**Fastening Type** Fixed

**Mounting Plate Dimensions** 2 3/8 in x 2 3/8 in (60 mm x 60 mm)

### DESCRIPTION

#### Non-marking rubber tread

Medium-duty caster. Scuff-free gray thermoplastic rubber with plate. Swivel with full locking brake.

### ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Metal thread guards - Corrosion-resistant zinc finish - Two independent rows of hardened polished precision ball bearings roll freely in large-diameter lubricated raceways

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F24815
<b>Mounting Type</b>	Plate
<b>Material</b>	TPR (Thermoplastic Rubber)
<b>Recommended Surfaces</b>	Concrete, Carpet, Steel, Wood/Planking, Tile/Ceramic/ Linoleum, Hardwood/Laminate
<b>Finish</b>	Gray
<b>Conditions</b>	Water, Solvents, Detergent, Extreme Heat, Petroleum Products

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

