



## **Industrial Gray Thermoplastic Rubber Caster**

**Product #** F25371

Load Capacity Per Caster Max. 135 kg

Wheel Diameter 127 mm

Total Height 156 mm

Fastening Type Swivel with Brake

**Mounting Plate Dimensions** 2 7/8 in x 3 5/8 in (73 mm x 92 mm)

### **DESCRIPTION**

Non-marking rubber tread

These heavy-duty casters are durable and designed for use in the most demanding environments. Available in three heights. Fixed or swivel design, with or without brakes

#### **ADVANTAGES AND BENEFITS**

- Non-marking rubber tread - Polypropylene rim resistant to nicks, scratches, stains, and deterioration - Thermoplastic rubber resistant to chemicals, caustics, oils, and wear - Corrosion-resistant zinc finish

#### **TECHNICAL SPECIFICATIONS**

Product #	F25371
Tread Width	32 mm
Mounting Type	Plate
Material	TPR (Thermoplastic Rubber)
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Gray
Conditions	Water, Solvents, Detergent, Acids, Extreme Cold, Petroleum Products

#### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

#### **DISCLAIMER**

Technical data subject to change without prior notice.



# PRODUCT PHOTOS





