



## Industrial Gray Thermoplastic Rubber Caster

**Product #** F25657

**Load Capacity Per Caster** Max. 135 kg

**Wheel Diameter** 127 mm

**Total Height** 156 mm

**Fastening Type** Swivel Without Brake

**Mounting Plate Dimensions** 2 7/8 in x 3 5/8 in (73 mm x 92 mm)

### DESCRIPTION

#### Non-marking rubber tread

These heavy-duty casters are durable and designed for use in the most demanding environments. Available in three heights. Fixed or swivel design, with or without brakes.

### ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Polypropylene rim resistant to nicks, scratches, stains, and deterioration - Thermoplastic rubber resistant to chemicals, caustics, oils, and wear
- Corrosion-resistant zinc finish

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F25657
<b>Tread Width</b>	32 mm
<b>Mounting Type</b>	Plate
<b>Material</b>	TPR (Thermoplastic Rubber)
<b>Recommended Surfaces</b>	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
<b>Finish</b>	Gray
<b>Conditions</b>	Water, Solvents, Detergent, Acids, Extreme Cold, Petroleum Products

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

