



## Industrial Black Phenolic Casters

**Product #** F26819

**Load Capacity Per Caster** Max. 260 kg

**Wheel Diameter** 100 mm

**Total Height** 135 mm

**Tread Width** 50 mm

**Fastening Type** Swivel Without Brake

**Axle Diameter** 20 mm

**Axle Length** 60 mm

**Features** With Lubrication Fittings

### DESCRIPTION

#### Non-marking rubber tread

These heavy-duty industrial black phenolic casters are suitable for extreme cold and extreme heat conditions. Available in fixed, swivel, or swivel with brake.

### ADVANTAGES AND BENEFITS

- Non-marking, non-conductive, and spark-proof
- High strength, high impact, resistance to oil, gasoline, and dilute acids
- Carbon steel top plate, heat-treated for extra strength
- Lubrication fitting for swivel raceway and wheel bearings

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F26819
<b>Mounting Type</b>	Plate
<b>Material</b>	Phenolic
<b>Recommended Surfaces</b>	Concrete, Carpet, Wood/Planking, Asphalt
<b>Finish</b>	Black
<b>Mounting Hole Diameter</b>	11 mm
<b>Mounting Plate Dimensions</b>	31 5/16 in x 4 1/2 in (100 mm x 115 mm)
<b>Conditions</b>	Extreme Cold, Extreme Heat, Petroleum Products, Dilute Acids

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents

### DISCLAIMER

Technical data subject to change without prior notice.

**PRODUCT PHOTOS**

---

