



Industrial Black Phenolic Casters

Product # F27116

Load Capacity Per Caster Max. 350 kg

Wheel Diameter 152 mm

Total Height 186 mm

Tread Width 45 mm

Fastening Type Fixed

Axle Diameter 16 mm

Axle Length 50 mm

Features Without Lubrication Fittings

DESCRIPTION

Non-marking rubber tread

These heavy-duty industrial black phenolic casters are suitable for extreme cold and extreme heat conditions. Available in fixed, swivel, or swivel with brake.

ADVANTAGES AND BENEFITS

- Non-marking, non-conductive, and spark-proof - High strength, high impact, resistance to oil, gasoline, and dilute acids - Carbon steel top plate, heat-treated for extra strength - Lubrication fitting for swivel raceway and wheel bearings

TECHNICAL SPECIFICATIONS

Product #	F27116
Mounting Type	Plate
Material	Phenolic
Recommended Surfaces	Concrete, Carpet, Wood/Planking, Asphalt
Finish	Black
Mounting Hole Diameter	11 mm
Mounting Plate Dimensions	31 5/16 in x 4 1/2 in (100 mm x 115 mm)
Conditions	Extreme Cold, Extreme Heat, Petroleum Products, Dilute Acids

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

