



Industrial Pneumatic Casters

Product # F27358

Load Capacity Per Caster Max. 120 kg

Wheel Diameter 254 mm

Total Height 300 mm

Tread Width 89 mm

Fastening Type Fixed

Tread Type Sawtooth

DESCRIPTION

Absorb shocks and vibrations

Industrial pneumatic casters. Absorbs shocks and vibration. Suitable for concrete, wood, asphalt, and gravel. Moves delicate loads smoothly and safely over rough surfaces.

ADVANTAGES AND BENEFITS

- Designed to absorb shocks and vibrations caused by floor obstructions or outdoor terrain - Moves delicate loads smoothly and safely over rough surfaces

TECHNICAL SPECIFICATIONS

Product #	F27358
Mounting Type	Plate
Material	Rubber
Recommended Surfaces	Concrete, Wood/Planking, Asphalt, Gravel
Finish	Black
Axle Diameter	16 mm
Axle Length	98 mm
Mounting Hole Diameter	10 mm
Mounting Plate Dimensions	3 15/16 in x 4 17/32 in (100 mm x 115 mm)
Conditions	Water

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to without prior notice.

PRODUCT PHOTOS

