



## Gray Thermoplastic Rubber Casters for General Use

### Load Capacity Per Caster

Max. 50 kg

Max. 75 kg

### Wheel Diameter

50 mm

75 mm

### Total Height

71 mm

100 mm

### Tread Width

18 mm

24 mm

### Fastening Type



Fixed


Swivel with  
Full Lock  
Brake

Swivel  
Without Brake

### Mounting Plate Dimensions

2 1/8 in x 2  
1/8 in (54 mm  
x 54 mm)

2 3/8 in x 2  
3/8 in (60 mm  
x 60 mm)

## DESCRIPTION

### Non-marking rubber tread

Medium-duty caster. Scuff-free gray thermoplastic rubber with plate. Swivel with full locking brake.

## ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Metal thread guards - Corrosion-resistant zinc finish - Two independent rows of hardened polished precision ball bearings roll freely in large-diameter lubricated raceways

## AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Mounting Plate Dimensions
<b>F24814</b>	Max. 50 kg	50 mm	71 mm	18 mm	Fixed	2 1/8 in x 2 1/8 in (54 mm x 54 mm)
<b>F24785</b>	Max. 50 kg	50 mm	71 mm	18 mm	Swivel with Full Lock Brake	2 1/8 in x 2 1/8 in (54 mm x 54 mm)
<b>F24784</b>	Max. 50 kg	50 mm	71 mm	18 mm	Swivel Without Brake	2 1/8 in x 2 1/8 in (54 mm x 54 mm)
<b>F24815</b>	Max. 75 kg	75 mm	100 mm	24 mm	Fixed	2 3/8 in x 2 3/8 in (60 mm x 60 mm)
<b>F24787</b>	Max. 75 kg	75 mm	100 mm	24 mm	Swivel with Full Lock Brake	2 3/8 in x 2 3/8 in (60 mm x 60 mm)
<b>F24786</b>	Max. 75 kg	75 mm	100 mm	24 mm	Swivel Without Brake	2 3/8 in x 2 3/8 in (60 mm x 60 mm)

## TECHNICAL SPECIFICATIONS

<b>Mounting Type</b>	Plate
<b>Material</b>	TPR (Thermoplastic Rubber)
<b>Recommended Surfaces</b>	Concrete, Carpet, Steel, Wood/Planking, Tile/Ceramic/ Linoleum, Hardwood/Laminate
<b>Finish</b>	Gray
<b>Conditions</b>	Water, Solvents, Detergent, Extreme Heat, Petroleum Products

## IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

## DISCLAIMER

Technical data subject to change without prior notice.

---

**PRODUCT PHOTOS**