

# Industrial Gray Thermoplastic Rubber Caster

#### Load Capacity Per Caster



#### Wheel Diameter




#### **Total Height**

| 98 mm | 99 mm | 126 mm | 155 mm | 156 mm |
|-------|-------|--------|--------|--------|

### **Fastening Type**



#### **Mounting Plate Dimensions**



## DESCRIPTION

#### Non-marking rubber tread

These heavy-duty casters are durable and designed for use in the most demanding environments. Available in three heights. Fixed or swivel design, with or without brakes.

# **ADVANTAGES AND BENEFITS**

- Non-marking rubber tread - Polypropylene rim resistant to nicks, scratches, stains, and deterioration - Thermoplastic rubber resistant to chemicals, caustics, oils, and wear - Corrosion-resistant zinc finish

# MADICO

# AVAILABLE PRODUCTS

| Product # | Load Capacity Per Caster | Wheel Diameter | Total Height | Fastening Type       | Mounting Plate Dimensions              |
|-----------|--------------------------|----------------|--------------|----------------------|--|
| F27274    | Max. 80 kg               | 76 mm          | 98 mm        | Fixed                | 2 1/2 in x 3 5/8 in (63.4 mm x 92 mm)  |
| F25621    | Max. 80 kg               | 76 mm          | 99 mm        | Swivel with Brake    | 2 9/16 in x 3 5/8 in (65 mm x 92 mm)   |
| F25655    | Max. 80 kg               | 76 mm          | 99 mm        | Swivel Without Brake | 2 9/16 in x 3 5/8 in (65 mm x 92 mm)   |
| F27275    | Max. 112 kg              | 102 mm         | 126 mm       | Fixed                | 2 29/32 in x 4 1/8 in (74 mm x 105 mm) |
| F25622    | Max. 112 kg              | 102 mm         | 126 mm       | Swivel with Brake    | 2 7/8 in x 3 5/8 in (73 mm x 92 mm)    |
| F25656    | Max. 112 kg              | 102 mm         | 126 mm       | Swivel Without Brake | 2 7/8 in x 3 5/8 in (73 mm x 92 mm)    |
| F27276    | Max. 135 kg              | 127 mm         | 155 mm       | Fixed                | 2 29/32 in x 4 1/8 in (74 mm x 105 mm) |
| F25371    | Max. 135 kg              | 127 mm         | 156 mm       | Swivel with Brake    | 2 7/8 in x 3 5/8 in (73 mm x 92 mm)    |
| F25657    | Max. 135 kg              | 127 mm         | 156 mm       | Swivel Without Brake | 2 7/8 in x 3 5/8 in (73 mm x 92 mm)    |

# **TECHNICAL SPECIFICATIONS**

| Tread Width          | 32 mm   |  |  |
|----------------------|---|--|--|
| Mounting Type        | Plate   |  |  |
| Material             | TPR (Thermoplastic Rubber)  |  |  |
| Recommended Surfaces | Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum,<br>Hardwood/Laminate |  |  |
| Finish               | Gray  |  |  |
| Conditions           | Water, Solvents, Detergent, Acids, Extreme Cold, Petroleum Products                   |  |  |

# **IMPORTANT INFORMATION**

For all additional measurements, please see the technical documents.

# DISCLAIMER

Technical data subject to change without prior notice.



# PRODUCT PHOTOS

