



Industrial Blue Elastic Rubber Caster

Load Capacity Per Caster

Max. 150 kg

Max. 180 kg

Max. 250 kg

Wheel Diameter

100 mm

125 mm

160 mm

Total Height

128 mm

155 mm

190 mm

Tread Width

35 mm

40 mm

45 mm

Fastening Type



Fixed


Swivel with
Double-Lock
Brake

Swivel
Without Brake

Axle Diameter

12 mm

15 mm

20 mm

Axle Length

40 mm

46 mm

59 mm

Mounting Hole Diameter

9 mm

11 mm

Mounting Plate Dimensions

3 11/32 in x 4
3/32 in (85
mm x 104
mm)

3 5/32 in x 4
1/8 in (80 mm
x 105 mm)

3 7/16 in x 4
in (87 mm x
102 mm)

4 11/32 in x 5
5/16 in (110
mm x 135
mm)

DESCRIPTION

Non-marking rubber tread

Blue non-marking runner tread. These heavy-duty casters are durable and designed for

use in the most demanding environments. Available in fixed or swivel design, with several braking options.

ADVANTAGES AND BENEFITS

- Double-lock braking system for both the wheel and the swivel (F08336, F08339, and F24800) - Non-marking rubber tread - Low starting effort, rolls easily; tread does not flat-spot - Metal thread guards - Grease seal to hold in lubricant - Corrosion-resistant zinc finish

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F08334	Max. 150 kg	100 mm	128 mm	35 mm	Fixed	12 mm	40 mm	9 mm	3 7/16 in x 4 in (87 mm x 102 mm)
F08336	Max. 150 kg	100 mm	128 mm	35 mm	Swivel with Double-Lock Brake	12 mm	40 mm	9 mm	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08335	Max. 150 kg	100 mm	128 mm	35 mm	Swivel Without Brake	12 mm	40 mm	9 mm	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08337	Max. 180 kg	125 mm	155 mm	40 mm	Fixed	15 mm	46 mm	9 mm	3 11/32 in x 4 3/32 in (85 mm x 104 mm)
F08339	Max. 180 kg	125 mm	155 mm	40 mm	Swivel with Double-Lock Brake	15 mm	46 mm	9 mm	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F08338	Max. 180 kg	125 mm	155 mm	40 mm	Swivel Without Brake	15 mm	46 mm	9 mm	3 5/32 in x 4 1/8 in (80 mm x 105 mm)
F24800	Max. 250 kg	160 mm	190 mm	45 mm	Swivel with Double-Lock Brake	20 mm	59 mm	11 mm	4 11/32 in x 5 5/16 in (110 mm x 135 mm)
F24789	Max. 250 kg	160 mm	190 mm	45 mm	Swivel Without Brake	20 mm	59 mm	11 mm	4 11/32 in x 5 5/16 in (110 mm x 135 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Elastic Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Blue
Conditions	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS