



Industrial Sintered Iron Caster

Load Capacity Per Caster

Max. 57 kg

Max. 80 kg

Max. 95 kg

Max. 115 kg

Wheel Diameter

50 mm

64 mm

76 mm

102 mm

Total Height

62 mm

82 mm

97 mm

125 mm

126 mm

Tread Width

22 mm

26 mm

28 mm

33.5 mm

Fastening Type



Fixed


Swivel
Without Brake

Axle Diameter

6.5 mm

8 mm

9 mm

11 mm

Axle Length

26 mm

35 mm

40 mm

51 mm

Mounting Hole Diameter

6.5 mm

7 mm

8 mm

8.5 mm

10 mm

13 mm

Mounting Plate Dimensions

1 1/2 in x 2
11/16 in (38
mm x 68 mm)

1 29/32 in x 2
9/16 in (48
mm x 65 mm)

2 7/16 in x 4
7/8 in (62 mm
x 124 mm)

2 7/32 in x 4
15/32 in (56
mm x 113
mm)

3 1/32 in x 6
1/8 in (77 mm
x 156 mm)

3 1/8 in x 4
1/8 in (79.5
mm x 105
mm)

3 7/8 in x 2
3/4 in (98 mm
x 70 mm)

4 1/16 in x 5
1/8 in (103
mm x 130
mm)

DESCRIPTION

High capacity and durability

Industrial sintered iron caster. Recommended for concrete, steel, and asphalt. Heavy-duty, available in two heights.

ADVANTAGES AND BENEFITS

- Non-marking rubber tread - High capacity and durability: Ideal for extreme operating temperatures - Powered iron, compacted and sintered to cast-iron strength, makes smooth tread - Corrosion-resistant zinc finish

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F24822	Max. 57 kg	50 mm	62 mm	22 mm	Fixed	6.5 mm	26 mm	7 mm	1 1/2 in x 2 11/16 in (38 mm x 68 mm)
F25028	Max. 57 kg	50 mm	62 mm	22 mm	Swivel Without Brake	6.5 mm	26 mm	6.5 mm	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F24830	Max. 80 kg	64 mm	82 mm	26 mm	Fixed	8 mm	35 mm	8.5 mm	2 7/32 in x 4 15/32 in (56 mm x 113 mm)
F24831	Max. 80 kg	64 mm	82 mm	26 mm	Swivel Without Brake	8 mm	35 mm	8 mm	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F24820	Max. 95 kg	76 mm	97 mm	28 mm	Fixed	9 mm	40 mm	8.5 mm	2 7/16 in x 4 7/8 in (62 mm x 124 mm)
F25049	Max. 95 kg	76 mm	97 mm	28 mm	Swivel Without Brake	9 mm	40 mm	8.5 mm	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F24832	Max. 115 kg	102 mm	125 mm	33.5 mm	Swivel Without Brake	11 mm	51 mm	13 mm	4 1/16 in x 5 1/8 in (103 mm x 130 mm)
F24834	Max. 115 kg	102 mm	126 mm	33.5 mm	Fixed	11 mm	51 mm	10 mm	3 1/32 in x 6 1/8 in (77 mm x 156 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Sintered Iron
Recommended Surfaces	Concrete, Steel, Asphalt
Finish	Metal
Conditions	Extreme Cold, Extreme Heat, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the line art and technical documents. Not recommended for applications in areas with high humidity.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

