



Industrial Black General-Duty Rubber Casters

Load Capacity Per Caster

Max. 15 kg	Max. 20 kg	Max. 57 kg	Max. 80 kg	Max. 95 kg
Max. 112 kg	Max. 135 kg			

Wheel Diameter

30 mm	40 mm	50 mm	63 mm	75 mm
102 mm	125 mm			




Total Height

38 mm	42 mm	51 mm	52 mm	62 mm
82 mm	97 mm	127 mm	155.5 mm	156 mm

Tread Width

13 mm	14 mm	17 mm	23 mm	27 mm
31.8 mm	32 mm	32.5 mm		

Fastening Type

		
Fixed	Swivel with Brake	Swivel Without Brake

Axle Diameter

1.5 mm	6.5 mm	8 mm	9 mm	10 mm
--------	--------	------	------	-------

Axle Length

25 mm	33 mm	34 mm	38.5 mm	40 mm
-------	-------	-------	---------	-------

Mounting Hole Diameter

4 mm	5 mm	5.5 mm	6.5 mm	7 mm
8 mm	8.5 mm	9 mm	10 mm	

Mounting Plate Dimensions

1 1/2 in x 2
11/16 in (38
mm x 68 mm)

1 17/32 in x 1
27/32 in (39
mm x 47 mm)

1 29/32 in x 2
9/16 in (48
mm x 65 mm)

1 9/32 in x 1
1/2 in (32 mm
x 38 mm)

2 17/32 in x 3
21/32 in (64
mm x 93 mm)

2 3/8 in x 3
5/8 in (60 mm
x 92 mm)

25/32 in x 1
15/32 in (20
mm x 37 mm)

2 7/16 in x 4
7/8 in (62 mm
x 124 mm)

2 7/32 in x 4
15/32 in (56
mm x 113
mm)

31/32 in x 1
13/16 in (25
mm x 46 mm)

3 1/8 in x 4
1/8 in (79.5
mm x 105
mm)

3 7/8 in x 2
3/4 in (98 mm
x 70 mm)

DESCRIPTION

Combines strength and durability

These industrial black general-duty rubber casters are suitable for surfaces that have water, petroleum, or by-products. Available in seven different heights.

ADVANTAGES AND BENEFITS

- Combines strength and durability - Soft rubber tread combined with hard rubber rim for motion stability

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F22902	Max. 15 kg	30 mm	38 mm	14 mm	Fixed	1.5 mm	33 mm	4 mm	25/32 in x 1 15/32 in (20 mm x 37 mm)
F22900	Max. 15 kg	30 mm	42 mm	13 mm	Swivel Without Brake	1.5 mm	33 mm	4 mm	1 9/32 in x 1 1/2 in (32 mm x 38 mm)
F22903	Max. 20 kg	40 mm	51 mm	17 mm	Fixed	1.5 mm	38.5 mm	5.5 mm	31/32 in x 1 13/16 in (25 mm x 46 mm)
F22904	Max. 20 kg	40 mm	51 mm	17 mm	Swivel with Brake	1.5 mm	38.5 mm	5 mm	1 17/32 in x 1 27/32 in (39 mm x 47 mm)
F22901	Max. 20 kg	40 mm	52 mm	17 mm	Swivel Without Brake	1.5 mm	38.5 mm	5 mm	1 17/32 in x 1 27/32 in (39 mm x 47 mm)
F25748	Max. 57 kg	50 mm	62 mm	23 mm	Fixed	6.5 mm	25 mm	7 mm	1 1/2 in x 2 11/16 in (38 mm x 68 mm)
F25086	Max. 57 kg	50 mm	62 mm	23 mm	Swivel with Brake	6.5 mm	25 mm	6.5 mm	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F25082	Max. 57 kg	50 mm	62 mm	23 mm	Swivel Without Brake	6.5 mm	25 mm	6.5 mm	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F25749	Max. 80 kg	63 mm	82 mm	27 mm	Fixed	8 mm	34 mm	8.5 mm	2 7/32 in x 4 15/32 in (56 mm x 113 mm)
F25160	Max. 80 kg	63 mm	82 mm	27 mm	Swivel with Brake	8 mm	34 mm	8 mm	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25083	Max. 80 kg	63 mm	82 mm	27 mm	Swivel Without Brake	8 mm	34 mm	8 mm	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25752	Max. 95 kg	75 mm	97 mm	32.5 mm	Fixed	9 mm	40 mm	8.5 mm	2 7/16 in x 4 7/8 in (62 mm x 124 mm)
F25095	Max. 95 kg	75 mm	97 mm	32.5 mm	Swivel with Brake	10 mm	40 mm	8.5 mm	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F25091	Max. 95 kg	75 mm	97 mm	32.5 mm	Swivel Without Brake	10 mm	40 mm	8.5 mm	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F27280	Max. 112 kg	102 mm	127 mm	32 mm	Fixed	10 mm	38.5 mm	9 mm	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25415	Max. 112 kg	102 mm	127 mm	32 mm	Swivel with Brake	10 mm	38.5 mm	10 mm	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F25413	Max. 112 kg	102 mm	127 mm	32 mm	Swivel Without Brake	10 mm	38.5 mm	10 mm	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F27281	Max. 135 kg	125 mm	155.5 mm	31.8 mm	Fixed	10 mm	40 mm	9 mm	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25533	Max. 135 kg	125 mm	155.5 mm	32 mm	Swivel Without Brake	10 mm	40 mm	9 mm	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25426	Max. 135 kg	125 mm	156 mm	32 mm	Swivel with Brake	10 mm	40 mm	9 mm	2 3/8 in x 3 5/8 in (60 mm x 92 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	General Duty Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

