



Euro Series Industrial Rubber Casters

Load Capacity Per Caster

Max. 50 kg

Max. 70 kg

Max. 100 kg

Max. 140 kg

Wheel Diameter

80 mm

100 mm

125 mm

160 mm

Total Height

105 mm

128 mm

155 mm

195 mm

Tread Width

25 mm

30 mm

37 mm

40 mm

Fastening Type



Fixed


Swivel with
Double-Lock
Brake

Swivel
Without Brake

Axle Diameter

12 mm

15 mm

20 mm

Axle Length

40 mm

49 mm

59 mm

Mounting Hole Diameter

8.5 mm

12 mm

Mounting Plate Dimensions

3 5/32 in x 4
1/32 in (80
mm x 102
mm)

4 11/32 in x 5
5/16 in (110
mm x 135
mm)

DESCRIPTION

Superior rolling quality

These Euro series industrial rubber casters are suitable for surfaces that have water,

detergent, petroleum, or by-products. Available with fixed, swivel, or double locking plate.

ADVANTAGES AND BENEFITS

- Metal thread guard - Double-lock braking system for both the wheel and the swivel (F24801, F24802, and F24803) - Grease seal holds in lubricant - Corrosion-resistant zinc finish - Fully seated ball bearing eliminates the need for axle lubrication, thus reducing maintenance costs - Two independent rows of hardened, polished precision ball bearings roll freely in large-diameter lubricated raceways

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Mounting Hole Diameter	Mounting Plate Dimensions
F24796	Max. 50 kg	80 mm	105 mm	25 mm	Fixed	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24801	Max. 50 kg	80 mm	105 mm	25 mm	Swivel with Double-Lock Brake	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24790	Max. 50 kg	80 mm	105 mm	25 mm	Swivel Without Brake	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24797	Max. 70 kg	100 mm	128 mm	30 mm	Fixed	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24802	Max. 70 kg	100 mm	128 mm	30 mm	Swivel with Double-Lock Brake	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24791	Max. 70 kg	100 mm	128 mm	30 mm	Swivel Without Brake	12 mm	40 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24798	Max. 100 kg	125 mm	155 mm	37 mm	Fixed	15 mm	49 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24803	Max. 100 kg	125 mm	155 mm	37 mm	Swivel with Double-Lock Brake	15 mm	49 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24792	Max. 100 kg	125 mm	155 mm	37 mm	Swivel Without Brake	15 mm	49 mm	8.5 mm	3 5/32 in x 4 1/32 in (80 mm x 102 mm)
F24788	Max. 140 kg	160 mm	195 mm	40 mm	Swivel Without Brake	20 mm	59 mm	12 mm	4 11/32 in x 5 5/16 in (110 mm x 135 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Euro Series Rubber
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt
Finish	Black
Conditions	Water, Detergent, Petroleum Products

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS