



## Industrial Pneumatic Casters

### Load Capacity Per Caster

Max. 100 kg

Max. 120 kg

Max. 140 kg

### Wheel Diameter

203 mm

254 mm

300 mm

### Total Height

254 mm

300 mm

400 mm

### Tread Width

64 mm

83 mm

89 mm

### Fastening Type



Fixed


Swivel  
Without Brake

### Tread Type

Diamond

Sawtooth

## DESCRIPTION

### Absorb shocks and vibrations

Industrial pneumatic casters. Absorbs shocks and vibration. Suitable for concrete, wood, asphalt, and gravel. Moves delicate loads smoothly and safely over rough surfaces.

## ADVANTAGES AND BENEFITS

- Designed to absorb shocks and vibrations caused by floor obstructions or outdoor terrain  
- Moves delicate loads smoothly and safely over rough surfaces

## AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Tread Type
<b>F27458</b>	Max. 100 kg	203 mm	254 mm	64 mm	Fixed	Sawtooth
<b>F26488</b>	Max. 100 kg	203 mm	254 mm	64 mm	Swivel Without Brake	Sawtooth
<b>F27358</b>	Max. 120 kg	254 mm	300 mm	89 mm	Fixed	Sawtooth
<b>F26552</b>	Max. 120 kg	254 mm	300 mm	89 mm	Swivel Without Brake	Sawtooth
<b>F27359</b>	Max. 140 kg	300 mm	400 mm	83 mm	Fixed	Diamond
<b>F26612</b>	Max. 140 kg	300 mm	400 mm	83 mm	Swivel Without Brake	Diamond

## TECHNICAL SPECIFICATIONS

<b>Mounting Type</b>	Plate
<b>Material</b>	Rubber
<b>Recommended Surfaces</b>	Concrete, Wood/Planking, Asphalt, Gravel
<b>Finish</b>	Black
<b>Axle Diameter</b>	16 mm
<b>Axle Length</b>	98 mm
<b>Mounting Hole Diameter</b>	10 mm
<b>Mounting Plate Dimensions</b>	3 15/16 in x 4 17/32 in (100 mm x 115 mm)
<b>Conditions</b>	Water

## IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

## DISCLAIMER

Technical data subject to without prior notice.

---

**PRODUCT PHOTOS**