



Pneumatic

Dynamic Load Capacity

Max. 100 kg

Max. 120 kg

Max. 140 kg

Wheel Diameter

200 mm

254 mm

330 mm

356 mm

406 mm

Color / Finish

Black

Black / Gray

Black / Red

Tread Width

60 mm

89 mm

102 mm

Tread Type

Knobby

Ribbed

Sawtooth

Hub Type

Centered

Off-centered

Hub Width

50 mm

52 mm

97 mm

152 mm

Hub Specification

Centered

Offset

Axle Length

50 mm

51 mm

97 mm

98 mm

152 mm

DESCRIPTION

Absorb shocks and vibrations

ADVANTAGES AND BENEFITS

- Designed to absorb shocks and vibrations caused by floor obstacles or irregularities. - Safely move fragile objects over uneven or rough surfaces.

AVAILABLE PRODUCTS

Product #	Dynamic Load Capacity	Wheel Diameter	Color / Finish	Tread Width	Tread Type	Hub Type	Hub Width	Hub Specification	Axle Length
F92154	Max. 100 kg	200 mm	Black / Gray	60 mm	Sawtooth	Centered	97 mm	Centered	97 mm
F20679	Max. 120 kg	254 mm	Black / Gray	89 mm	Knobby	Off-centered	52 mm	Offset	50 mm
F92152	Max. 120 kg	254 mm	Black / Gray	89 mm	Sawtooth	Centered	97 mm	Centered	98 mm
F20680	Max. 120 kg	330 mm	Black / Gray	102 mm	Knobby	Off-centered	52 mm	Offset	51 mm
F20683	Max. 120 kg	356 mm	Black	102 mm	Knobby	Centered	50 mm	Centered	51 mm
F20578	Max. 140 kg	406 mm	Black / Red	102 mm	Ribbed	Centered	152 mm	Centered	152 mm

TECHNICAL SPECIFICATIONS

Recommended Surfaces	Asphalt, Concrete, Wood/Planking, Gravel
Fastening Type	Fixed
Material	Rubber
Axle Diameter	16 mm
Hub Material	Metal

IMPORTANT INFORMATION

For additional measurements, please see the technical documents

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS