



Semi-Pneumatic - Metal Hub

Dynamic Load Capacity

Max. 50 kg

Max. 65 kg

Max. 80 kg

Max. 100 kg

Wheel Diameter

150 mm

152 mm

175 mm

178 mm

200 mm

203 mm

250 mm

255 mm

Tread Width

38 mm

44 mm

44.5 mm

61 mm

Tread Type

Diamond

Ribbed

Axle Diameter

12 mm

13 mm

16 mm

Hub Type

Centered

Off-centered

Hub Width

35 mm

36 mm

47 mm

50 mm

61 mm

Hub Specification

Steel/Centered

Steel/Offset

Axle Length

24.5 mm

35 mm

37 mm

50 mm

51 mm

70 mm

Bearing

Ball

Roller

DESCRIPTION

Puncture-proof, metal hub

ADVANTAGES AND BENEFITS

Impact-resistant Puncture-proof wheels

AVAILABLE PRODUCTS

Product #	Dynamic Load Capacity	Wheel Diameter	Tread Width	Tread Type	Axle Diameter	Hub Type	Hub Width	Hub Specification	Axle Length	Bearing
F20716	Max. 50 kg	150 mm	38 mm	Ribbed	13 mm	Centered	50 mm	Steel/Centered	50 mm	Ball
F20708	Max. 50 kg	152 mm	38 mm	Diamond	12 mm	Off-centered	35 mm	Steel/Offset	35 mm	Ball
F20709	Max. 50 kg	152 mm	38 mm	Diamond	13 mm	Centered	50 mm	Steel/Centered	24.5 mm	Ball
F20717	Max. 65 kg	175 mm	38 mm	Ribbed	13 mm	Centered	50 mm	Steel/Centered	50 mm	Ball
F20713	Max. 65 kg	178 mm	38 mm	Diamond	12 mm	Off-centered	35 mm	Steel/Offset	35 mm	Ball
F20712	Max. 65 kg	178 mm	38 mm	Diamond	13 mm	Centered	50 mm	Steel/Centered	51 mm	Ball
F20718	Max. 80 kg	200 mm	44 mm	Ribbed	13 mm	Centered	50 mm	Steel/Centered	50 mm	Ball
F20703	Max. 80 kg	203 mm	44 mm	Diamond	13 mm	Centered	50 mm	Steel/Centered	51 mm	Ball
F20704	Max. 80 kg	203 mm	44.5 mm	Diamond	12 mm	Off-centered	36 mm	Steel/Offset	37 mm	Ball
F20200	Max. 80 kg	250 mm	61 mm	Ribbed	16 mm	Centered	61 mm	Steel/Centered	70 mm	Roller
F20147	Max. 100 kg	255 mm	44 mm	Ribbed	13 mm	Centered	47 mm	Steel/Centered	50 mm	Ball

TECHNICAL SPECIFICATIONS

Recommended Surfaces	Asphalt, Steel/Grills, Concrete, Tile/Ceramic/Linoleum, Wood/Planking, Gravel, Grass
Color / Finish	Black, Red
Fastening Type	Fixed
Material	Rubber
Hub Material	Metal

IMPORTANT INFORMATION

For additional measurements, please see the technical documents

DISCLAIMER

Technical data subject to without prior notice.

PRODUCT PHOTOS