



### **Semi-Pneumatic - Plastic Hub**

### **Dynamic Load Capacity**

Max. 50 kg | Max. 65 kg | Max. 80 kg | Max. 100 kg | Max. 120 kg

#### **Wheel Diameter**

152 mm 178 mm 203 mm 252 mm 254 mm

#### Color / Finish

Black / Gray Black / White

#### **Tread Width**

38 mm 40 mm 44 mm 54 mm 55 mm

## **Tread Type**

Diamond Ribbed

#### **Axle Diameter**

12 mm 13 mm 16 mm

#### **Hub Width**

40 mm 53 mm 55 mm

### **Axle Length**

40 mm 54 mm 55 mm

### **Bearing**

Ball Plain

#### **DESCRIPTION**

Impact-resistant and puncture-proof



## **AVAILABLE PRODUCTS**

Product #	Dynamic Load Capacity	Wheel Diameter	Color / Finish	Tread Width	Tread Type	Axle Diameter	Hub Width	Axle Length	Bearing
F42032	Max. 50 kg	152 mm	Black / White	38 mm	Diamond	13 mm	40 mm	40 mm	Plain
F42033	Max. 65 kg	178 mm	Black / White	38 mm	Diamond	12 mm	40 mm	40 mm	Plain
F42034	Max. 80 kg	203 mm	Black / White	44 mm	Diamond	12 mm	40 mm	40 mm	Plain
F42108	Max. 100 kg	203 mm	Black / Gray	55 mm	Ribbed	16 mm	55 mm	55 mm	Ball
F42009	Max. 100 kg	252 mm	Black / White	40 mm	Diamond	13 mm	40 mm	40 mm	Plain
F42110	Max. 120 kg	254 mm	Black / Gray	54 mm	Ribbed	16 mm	53 mm	54 mm	Ball

## **TECHNICAL SPECIFICATIONS**

Recommended Surfaces	Asphalt, Steel/Grills, Concrete, Tile/Ceramic/Linoleum, Wood/Planking, Gravel, Grass				
Fastening Type	Fixed				
Material	Rubber				
Hub Material	Plastic				
Hub Type	Off-centered				
Hub Specification	Plastic/Offset				

# PRODUCT PHOTOS

