



Heavy-Duty Mold-On Polyurethane Industrial Casters with Plate

Load Capacity Per Caster




Wheel Diameter

100 mm	125 mm	160 mm	200 mm

Total Height

140 mm	166 mm	186 mm	236 mm

Fastening Type



DESCRIPTION

Durable heavy-duty casters. Designed for use in the most demanding environments. Available in four heights. Also offered with three types of plate: fixed, swivel, or swivel with brake.

ADVANTAGES AND BENEFITS

- Excellent combination of strength and durability (resistant to oil and chemicals) - Soft and smooth ball bearing that will not scuff up floors - Weight capacity: from 200 kg (440 lb) to 350 kg (770 lb) per caster - Recommended surfaces: concrete, steel, tiles and hardwoods - Lubricant valve for all casters

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Fastening Type
F25004	300 kg	100 mm	140 mm	Fixed
F25204	300 kg	100 mm	140 mm	Swivel with Brake
F25104	300 kg	100 mm	140 mm	Swivel Without Brake
F25005	320 kg	125 mm	166 mm	Fixed
F25205	320 kg	125 mm	166 mm	Swivel with Brake
F25105	320 kg	125 mm	166 mm	Swivel Without Brake
F25006	350 kg	160 mm	186 mm	Fixed
F25206	350 kg	160 mm	186 mm	Swivel with Brake
F25106	350 kg	160 mm	186 mm	Swivel Without Brake
F25008	400 kg	200 mm	236 mm	Fixed
F25208	400 kg	200 mm	236 mm	Swivel with Brake
F25108	400 kg	200 mm	236 mm	Swivel Without Brake

TECHNICAL SPECIFICATIONS

Tread Width	50 mm	
Mounting Type	Plate	
Material	Polyurethane	
Recommended Surfaces	Concrete, Steel, Wood/Planking, Asphalt, Tile/Ceramic/ Linoleum, Hardwood/Laminate	
Finish	Red	
Brand	Madico	
Mounting Plate Dimensions	Dimensions 4 17/32 in x 4 1/32 in (115 mm x 102 mm)	
Features	Polyurethane Molded on Steel	
Conditions	Extreme Temperatures	

APPLICATION

- Carts - Machinery - Workbenches - Industrial and institutional equipment



PRODUCT PHOTOS

