



Industrial Casters for General Use

Load Capacity Per Caster

50 kg

75 kg

Wheel Diameter

50 mm

64 mm

75 mm

Total Height

64 mm

83 mm

94 mm

Tread Width

22 mm

23 mm

24 mm

Fastening Type


Swivel with
Brake

Swivel
Without Brake

Threaded Stem

3/8" - 16 × 1"

3/8" - 16 × 1-
1/2"

DESCRIPTION

Premium quality motion solutions

These medium-duty casters feature a scuff-free gray thermoplastic rubber with stem. Available with or without a brake.

ADVANTAGES AND BENEFITS

Non-marking rubber tread Increased load capacity Better quality caster material (TPR)
Thread guards

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Threaded Stem
F24723	50 kg	50 mm	64 mm	22 mm	Swivel with Brake	3/8" - 16 × 1"
F24722	50 kg	50 mm	64 mm	22 mm	Swivel Without Brake	3/8" - 16 × 1"
F24713	50 kg	64 mm	83 mm	24 mm	Swivel with Brake	3/8" - 16 × 1-1/2"
F24712	50 kg	64 mm	83 mm	24 mm	Swivel Without Brake	3/8" - 16 × 1-1/2"
F24733	75 kg	75 mm	94 mm	23 mm	Swivel with Brake	3/8" - 16 × 1-1/2"
F24732	75 kg	75 mm	94 mm	23 mm	Swivel Without Brake	3/8" - 16 × 1-1/2"

TECHNICAL SPECIFICATIONS

Mounting Type	Threaded Stem
Material	TPR (Thermoplastic Rubber)
Recommended Surfaces	Tile/Ceramic/ Linoleum, Hardwood/Laminate
Finish	Gray
Brand	Madico

APPLICATION

For hard surface floors, such as hardwood flooring, floating flooring, tiles and ceramics. Perfect for interior applications in the kitchen, living room or office.

IMPORTANT INFORMATION

Dimensions given in metric are exact; approximate in imperial. Technical data is subject to change without prior notice.

DISCLAIMER

Responsibility is limited to the cost of the product.

PRODUCT PHOTOS